

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>G06T 7/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/04498</b> <b>(43) International Publication Date:</b> 27 January 2000 (27.01.00)
<b>(21) International Application Number:</b> PCT/EP99/04767 <b>(22) International Filing Date:</b> 7 July 1999 (07.07.99)  <b>(30) Priority Data:</b> 09/116,769 16 July 1998 (16.07.98) US  <b>(71) Applicant:</b> KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).  <b>(72) Inventors:</b> MARTINO, Jacquelyn, A.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DIMITROVA, Nevenka; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). ELEN-BAAS, Jan, H.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). RUTGERS, Job; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).  <b>(74) Agent:</b> FAESSEN, Louis, M., H.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).		<b>(81) Designated States:</b> IN, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> A HISTOGRAM METHOD FOR CHARACTERIZING VIDEO CONTENT  <b>(57) Abstract</b>  In order to characterize video content, key frames are identified in that content. The key frames are collapsed into histograms. The histograms are grouped into families. The families are each represented by a family histogram. The family histograms characterize the video content. The family histograms can be used to determine program boundaries or index the video content.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A histogram method for characterizing video content.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The invention relates to the field of digital image processing and in particular to characterizing video content.

5

### 2. Related Art

US Pat. No. 5,179,832 teaches using some types of data in the video data stream to find scene changes. Scene changes are determined by comparison of data in consecutive frames.

## 10 SUMMARY OF THE INVENTION

The object of the invention is to create a useful characterization of video content.

This object is achieved by extracting key frames, grouping the key frames into families and creating a family representation. Preferably, the family representation is in the  
15 form of a histogram.

The family representation can be used to distinguish program boundaries, index tapes, identify program material, edit video content, or search video content for instance as part of a web search engine.

## 20 BRIEF DESCRIPTION OF THE DRAWING

Fig. 1 is a high level view of the system in accordance with the invention.

Fig. 2 is a flow chart showing operation of the invention.

Fig. 3 shows grouping of video material into key frames, families, and  
25 programs.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS.

Fig. 1 shows a system including the invention. A processor 103 is hooked to a user output device 101, a user input device 102, and a memory device 104. The memory  
5 stores digital video frame data and data abstracted from frames. The processor may optionally be connected via a communication link 106 and a network 105 to some remote device (not shown). The communication link may be wired or wireless and may lead to the remote device in some way other than through a network. The network may be the internet.

Fig. 2 shows a flow chart describing operation of the preferred embodiment of  
10 invention.

In box 201, a key frame is located and its frame number stored. The frame number associated with each key frame must be retained throughout the procedure. Identification of key frames can be done in accordance with US patent application serial numbers 08/867,140 and 08/867,145, which are incorporated herein by reference.

15 In box 202, a histogram is derived for the key frame. Deriving histograms from video frames is described in R. C. Gonzalez and R. E. Woods, Digital Image Processing, (Addison Wesley 1992) pp. 235-247. Basically every image is described by a number of colors, called a palette. The number of colors in the palette can be chosen in accordance with the application. The histogram gives a numerical value for each color. The numerical value is  
20 the number of pixels with that color in the key frame. Each histogram must be associated with a frame number.

For speed of processing, it is preferred, for the purposes of the invention, to choose a less than exhaustive palette. Colors such as black, white, and skin tones, which are likely to appear in all frames, are preferably not chosen for the palette, or are given a low  
25 weight. In the less than exhaustive palette, each chosen color is referred to as a "bin." For instance, the following bins might be used:

Bin name	Minimum hue degree	Maximum hue degree	Minimum percent saturation	Maximum percent saturation	Minimum percent lightness	Maximum percent lightness
Green01	67	146	7	100	10	95
Blue 01	147	244	14	100	15	93
Violet 01	245	330	8	100	5	98
Red 01	331	359	13	100	5	98
Red 02	0	3	13	100	5	98
Orange 01	4	42	15	100	5	97
Yellow 01	43	66	15	100	4	98

This set of bins is chosen according to a commonly used color space, but any color space might be used, e.g., HSV, YUV, RGB. More information about histogram formation is to be found in R. C. Gonzalez and RE Woods, Digital Image Processing, (Addison Wesley 1992) pp. 171-182. The set given above includes eight bins, but other numbers of bins might be used. Also, other definitions of the bins might be used, according to what the designer finds most effective. The different bins may be assigned different weights according to how important they are considered to be, so the weights may be considered an additional column in the above table.

After a histogram is defined for the key frame, based on the color of bins, the key frame is compared with any stored key frames at 203. This comparison is in accordance with the following formula:

$$difference(H_i, H_{i-1}) = \sum_j (w_i * v_j * |H_i(j) - H_{i-1}(j)|) < Threshold \quad (1)$$

In this formula, the variable  $H_i$  represents the histogram associated with the key frame of index  $i$ . The vector value  $H_i(j)$  is the numerical value of this histogram associated with bin of index  $j$ . The variable  $Threshold$  represents a value below which two histograms are to be considered similar.

The variable  $v_j$  is a weight associated with the bin of index  $j$ . If all bins are considered to have the same weight, then this bin weight can be omitted from formula 1.

The variable  $w_i$  represents a weight to be assigned to a key frame of index  $i$ . It should be noted that key frames associated with scenes of extremely short duration should be given low weight, as these scenes are probably not significant to the program and may even

represent commercials. Thus very short scenes should probably not be considered as being different from the scenes that precede them and should not be grounds for starting a new family, per the following step.

If the short scenes are never to be used for any purpose, it may be more efficient simply to test for scene length after box 201; and, if scene length is insufficient, control could be returned to box 201, without proceeding to the rest of the flow chart.

Formula (1) is only one of many ways of calculating a distance between histograms. Other ways of calculating such distances are discussed in S. Antani et al., Pattern Recognition Methods in Image and Video Databases: Past, Present and Future, Proceedings 7<sup>th</sup> International Workshop on Structural and Syntactic Pattern Recognition and 2<sup>nd</sup> International Workshop on Statistical Techniques in Pattern Recognition (Aug. 1998) Sydney, Australia, pre-published on the internet at [http://machine\\_vision.cse.psu.edu/~antani/pubs.html](http://machine_vision.cse.psu.edu/~antani/pubs.html) on 7/9/98

At 205 there is a branch. If the difference calculated according to formula (1) is less than Threshold, then the key frame represented by the current histogram is to be grouped into a stored family at 204. If the difference is greater than the stored threshold, a new family is formed at 206. New families are formed at 206 or histograms grouped into current families, only if the duration of the scene associated with the current histogram is considered sufficient, e.g., more than one minute.

At 206, a new family is formed. This family is a data structure which includes a family histogram, a total duration, and pointers to the constituent histograms and frame numbers. Each family histogram is formed by a data structure with pointers to each of the constituent histograms and frame numbers; a family histogram, initialized to the current histogram; and a variable representing total duration, which is initialized to the duration of the scene represented by the current histogram.

At 204, family histograms are grouped according to the following formula:

$$H_{fam}(\ell) = \sum_i \left( \frac{dur_i}{total\_dur_{fam}} \cdot H_i(\ell) \right) \quad (2)$$

In this formula

• is a variable representing the bin number;

fam is an index representing this particular family;

H<sub>fam</sub> is a vector representing the family histogram;

$i$  is an index representing the scene number. This index starts at 1 for the first scene added to the family and runs through the number of scenes in the family, including the current one being added.

$dur_i$  is a variable representing the duration of scene  $i$ . This duration is obtained by subtracting the frame number corresponding to the following key frame  $i+1$  from the frame number of the current key frame  $i$ ;

$H_i(\bullet)$  is the numerical value indicating the number of pixels in bin  $\bullet$  for key frame number  $i$ ; and

$total\_dur_{fam}$  is a variable representing the total duration of all scenes already in the family.

10 This variable must be updated by adding the duration of the scene associated with the current histogram, prior to making the calculation of formula (2).

At 207 it is tested whether all key frames have been found. If not, control returns to box 201. If so, each family is now represented by a single histogram, which is used for comparison purposes when new key frames are detected in a stream of video content. It would be expected that most half hour programs could be represented by about 3 families of histograms, though more or less could be used depending on the programming in question. A longer show might need more. Families of key frames characterizing a program can be built on the fly in accordance with the invention. Alternatively, families of key frames might be pre-stored corresponding to existing programs that a user might want to identify.

20 Once families are created, they can be used for numerous purposes. One is that the families can be used to distinguish program boundaries.

Fig. 3 shows video information grouped into key frames, represented by histograms. In this example, the histograms are called  $H_1, H_2, H_3, H_4, H_5, H_6, H_7$ , and  $H_8$ . Real video information could have more or less key frames. Certain of the histograms are grouped into families. For instance,  $H_1$  and  $H_4$  are both in a family represented by histogram  $H_{1,4}$ ;  $H_3$  and  $H_5$  are both in a family represented by histogram  $H_{3,5}$ ; and  $H_7$  and  $H_8$  are both in a family represented by histogram  $H_{7,8}$ . The histograms  $H_2$  and  $H_6$  are categorized as "disruptive." In other words, the video duration associated with those key frames is so short that they are not considered useful in identifying programming. Accordingly, their weights  $w_2$  and  $w_6$  in equation (1) will be low AND they will not be put into families according to boxes 204 and 206 of Fig. 2. The formation of these families is in accordance with boxes 204, 205 and 206 in Fig. 2.

The indices illustrated in the figures are purely examples. More or less indices of different values could be used by those of ordinary skill in the art depending on the actual video content.

A program boundary is placed between  $H_7$  and  $H_6$  in accordance with box 209  
5 of Fig. 2.

The family histograms  $H_{1,4}$  and  $H_{3,5}$  could then constitute a characterization of the first program. These family histograms could be stored for searching for programming on a database or on a VCR

Another possible use of the families of histograms is to compare programs.  
10 Boundaries of programs could be found in accordance with Fig. 3.

Alternatively, program boundaries could be determined manually. An algorithm for finding program boundaries follows:

\*\*\*\*\*

Let  $F_i$  be FamilyGroup  $i$  in the list of FamilyGroups  $F$ .  $n$  is the size of the list of FamilyGroups  
15

$\text{MIN}(F_i)$  is the minimum keyframeNr in the FamilyGroup  $F_i$ .

$\text{MAX}(F_i)$  is the maximum keyframeNr in the FamilyGroup  $F_i$ .

Algorithm

20

Assumption:  $F$  is sorted on  $\text{MIN}(F_i)$

FOR ( $i=0$ ;  $i < n-1$ ;  $i++$ )

DO

25  $j=i+1$ ;

IF ( $(\text{MAX}(F_i) < (\text{MIN}(F_j)))$

THEN

BoundaryBegin =  $\text{MAX}(\text{MIN}(F_j), \text{BoundaryBegin})$

BoundaryEnd =  $\text{MAX}(\text{MAX}(F_j), \text{BoundaryEnd})$

30 ELSE

BoundaryBegin =  $\text{MAX}(\text{MIN}(F_j), \text{BoundaryBegin})$

BoundaryEnd =  $\text{MAX}(\text{MAX}(F_j), \text{BoundaryEnd})$

ENDIF

IF ( $\text{BoundaryEnd} < \text{BoundaryBegin}$ )



THEN

PRINT 'Found a BOUNDARY between BoundaryEnd and BoundaryBegin'

ENDIF

DONE

5 PRINT 'BOUNDARY at n (end of video)'

\*\*\*\*\*

After program boundaries and families are determined, let us say that program S is characterized by four family histograms

$$SH = (SH_1, SH_2, SH_3, SH_4)$$

and let us say that program B is characterized by four family histograms

$$BH = (BH_1, BH_2, BH_3, BH_4)$$

Then the difference between two programs can be calculated according to the following formula

$$Diff(SH, BH) = \sum_i \left( \min_j D(SH_i, BH_j) \right) \quad (3)$$

Where

$$D(H_i, H_j) = \sum_k |H_i(k) - H_j(k)| \quad (4)$$

and where  $H_i(k)$  is the value in bin  $k$  of histogram  $H_i$ . Alternatively, weights could be applied to certain families if those were considered particularly important for characterizing the program, in which case the function  $D$  could be defined according to the following formula.

$$D(H_i, H_j) = \sum_i |H_i(k) * w_i - H_j(k) * w_j| \quad (5)$$

The differences between programs could be used in searching databases of video content or the world wide web. Alternatively, the differences could be used for marking programming suspected to not be what it is supposed to be, e.g., if pre-emptive programming were inserted into a video stream rather than scheduled programming. In such a case, the user might want to skip or pay particular attention to pre-emptive programming. Program comparison might even be used to identify unwanted programming for deletion from a database of video content.

In characterizing a series of programs, it may be useful to develop super-histograms for the series. In such a case, formula (2) can be used to combine scenes from several programs from the series to result in families that characterize all of the several programs. Such super-histograms could then be used to search for programs of that series in a database or stream of video content.

## CLAIMS:

1. A digital data processing method for characterizing video content, the method comprising executing the following operations in a digital data processing device (103):
  - a. extracting (201) key frames from the video content, each respective key frame representing a respective scene in the video content;
  - 5 b. grouping (204, 206) at least some of the key frames into at least one family of key frames;
  - c. establishing a respective family representation for the family;
  - d. embodying at least one such family representation in a storage medium to yield a characterization of the video content, the storage medium being readable by the digital data
  - 10 processing device.
2. The method of claim 1
  - a. further comprising the step of collapsing (200) each respective key frame into a plurality of bins to yield a respective histogram for each key frame;
  - 15 b. wherein the grouping operation comprises grouping significant key frames based on a comparison (203, 205) of the respective histograms;
  - c. wherein the family representation is a family histogram; and
  - d. wherein the characterization comprises at least one such family histogram.
- 20 3. The method of claim 2 wherein the grouping operation further comprises
  - a. comparing (203) each new key frame in a series with at least one family histogram to yield a difference measurement; and
  - b. if the difference measurement exceeds a predetermined threshold value determining (206) that the new key frame does not fall within the at least one family.
  - 25
4. A storage medium (104) readable by the digital data processing device embodying a characterization of video content produced according to the method of claim 1.

5. A digital data processing device (103) comprising the storage medium (104) of claim 4 and a digital data processor for processing data stored on the storage medium.
6. The digital data processing device of claim 5 wherein the digital data processor is adapted to index video content based on the characterization.
7. The digital data processing device of claim 5 wherein the digital data processor is adapted to search for video content based on the characterization.
8. The digital data processing device of claim 5 wherein the digital data processor is adapted to determine program boundaries based on the video content.
9. The digital data processing device of claim 5 comprising a communication link (106) adapted to allow browsing of the medium from a remote device.
10. The digital data processing device of claim 9 wherein the communication link (106) comprises an internet connection.

1/3




FIG. 1




FIG. 2

3/3




FIG. 3

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/04767

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G06T7/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, Y	US 5 805 733 A (NORMILE JAMES ET AL) 8 September 1998 (1998-09-08) abstract column 1, line 53 - line 59 column 2, line 5 - line 13 column 4, line 17 - line 24 ---	1-8
Y	EP 0 690 413 A (INST OF SYSTEMS SCIENCE) 3 January 1996 (1996-01-03) abstract page 3, line 2 - line 5 page 3, line 50 - line 59 -----	1-8

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 October 1999

Date of mailing of the international search report

02/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

González Arias, P



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/04767

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5805733 A	08-09-1998	NONE	
EP 0690413 A	03-01-1996	US 5635982 A JP 8237549 A	03-06-1997 13-09-1996